



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



VIAL – ACUA – 565 -S WATER-BASED SPECIAL PAINT FOR ASPHALT

PRODUCT DESCRIPTION:

- **DEFINITION:** It is a paint mixture of styrene resin of high covering and outdoor resistance.
- **USE:** Especially suitable for marking on cement floors and concrete. It is very suitable to paint lines on asphalt floors.
- **PROPERTIES:** Ideal product due to its exterior resistance and withstand all types of road traffic. Once the film dries, it can get an excellent resistance, opacity and adhesion.

TECHNICAL INFORMATION

Aspect..... SATIN OR MATTE
 Color..... ALL COLORS
 Density..... 1,26 Kg/Lt.
 Viscosity..... 115 – 125 K.U. 25° C
 Theoretical performance..... 7 - 9 M²/Kg.
 Drying 20 °C/70% RH
 Touch..... 1 HOUR
 Overall..... 4 HOURS
 Repaint..... IMMEDIATE

APPLICATION INSTRUCTIONS:

- **Brush and roller**
The first coat is diluted approximately to 5%. The second as it is.
- **Airbrush gun**
It is diluted to the necessary amount to adjust the viscosity.
Pressure: 3 – 4 Kg/cm² **Nozzle:** 1,8 – 2,2 mm.
- **Cleaning material and dilution**
Clean with tap water immediately after use.

SURFACES PREPARATION:

It should be remove any contamination such as dirt, grease, oil, old paint, and all kinds of dirt. In cases where there is a lot of dust it is advisable to vacuum.

HYGIENE AND SECURITY:

- Non-flammable product.
- Because contain no toxic product, no precautions are necessary in this regard.
- It should not be applied in cold weather where there are temperatures below or close to 5 ° C.
Preserves the paint can of frost.
- The storage lasts up to 2 years without any problems.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.