



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959  
POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)  
TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16  
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS  
E-mail: eupines@terra.es



## EMULEX - 75

### PRODUCT DESCRIPTION:

- **DEFINITION:** Is a high covering and resistance plastic painting, ideal for decoration and protection of interior and exterior surfaces.
- **USE:** On masonry surfaces (plaster, cement, tile, concrete...) as well as metal and wood (with previous preparation and priming).
- **PROPERTIES:** It is a painting based on a stable dispersion of pigments in an acrylic resin emulsion. Once the film is dry, it can achieve an excellent water resistance, opacity, whiteness and adhesion.

### TECHNICAL INFORMATION

Aspect..... SATIN  
 Color..... WHITE  
 Density..... 1,3 Kg/Lt.  
 Viscosity..... 110 - 120 K.U. 25°C  
 Theoretical performance..... 8 - 10 M<sup>2</sup>/Kg.  
 Drying 20 °C/70% RH  
 Touch..... 1 HOUR  
 Repaint..... 4 HOURS

### APPLICATION INSTRUCTIONS:

- **Brush and roller**  
The first coat is diluted to about 20% and the second at 5 or 10%.
- **Airbrush gun**  
It is diluted with the amount necessary to adjust the viscosity.  
**Pressure:** 3 - 4 Kg/cm<sup>2</sup> **Nozzle:** 1,5 - 2 mm.
- **Cleaning material and dilution**  
Clean with water immediately after use.

### SURFACES PREPARATION:

Remove imperfections and adhesions, sanding and cleaning to remove salt, grease, old paint, dust...

- **NEW SURFACES:**
  - 1 - **HARD AND DRY surfaces indoor and outdoor masonry.**  
Apply TWO COATS (the first diluted to 20% and the second one at 5 or 10%).
  - 2 - **SOFT SURFACES (plaster badly forged) or VERY ABSORBENT:**  
Give a good preparation to fill the pores with a Sandstone Sealant or Vitro Sealer and then TWO COATS of EMULEX-75
  - 3 - **WOOD.**  
Previously apply ONE COAT of VITREN SEALER and after ONE or TWO COATS of EMUCRYL - 75.
  - 4 - **Iron.**  
Previously apply one coat of PRIMER and passed 24 hours TWO COATS of EMUCRYL - 75

#### **Repaints over tempera, old paints, etc.**

After removing flakes, tempera, whitewash,... apply TWO COATS of EMUCRYL - 75.

### HYGIENE AND SECURITY:

- Nonflammable product.
- Because it contains no toxic products, it's not necessary to take precautions in this aspect.  
In case it will apply by gun, it is recommended use a mask.
- Avoid prolonged inhalation of solvent vapors.
- Do not use in cold weather where temperatures use to be near or less than 0°C.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.