



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



ANTINSECT SPECIAL PAINT

PRODUCT DESCRIPTION:

- **DEFINITION:** It is an acrylic paint ideal for decoration and protection of interior surfaces, synthetic pyrethroid based.
- **USE:** On masonry surfaces (plaster, plasterboard, cement, brick, concrete ...) and wood and metal (with previous preparation and primer required), easy extension and application.
- **PROPERTIES:** It is a painting based on a stable pigment dispersion on an acrylic resin emulsion. Once the film is dry it gets an excellent water resistance, optimum opacity, whiteness and adhesion. Exerts a strong insecticidal action on FLIES, SPIDERS, MOSQUITOES and other insects, it is performed both, by contact and ingestion and acts on different biological states thereof from eggs to adults. Have a high insecticidal activity and a very long residual effect. It is photostable and does not degrade in contact with water.

TECHNICAL INFORMATION

Aspect..... MATTE
 Color..... WHITE
 Density..... 1,5 Kg/Lt.
 Viscosity..... 110 – 120 K.U.
 Theoretical performance..... 8 - 10 M²/Kg.
 Drying 20 °C/70% RH
 Touch..... 1 HOUR
 Repaint..... 4 HOURS

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun or Air-Less.
- **Dilution**
If necessary use water.
- **Cleaning**
After use, clean all equipment with water

SURFACES PREPARATION:

- **NEW SURFACES.**
 - 1 - In hard and dry surfaces apply two coats (the first diluted about 20%, the second from 5 to 10%).
 - 2 - On soft surfaces, provide a good preparation to plug the pores, with **Latex Sealant - Alkyl**, or **Vitren Sealer** and then two coats of **Mosquitoes Repellent**.
 - 3 - For wood, previously apply one coat of **Vitren Sealer** and after that, one or two coats of **Mosquitoes Repellent**.
 - 4 - In iron, beforehand apply a primer and after 24 hours one or two coats of **Mosquitoes Repellent**.
- **OLD SURFACES.**
After removing the peeling, tempera, chalk, etc. apply two coats of **Mosquitoes Repellent**.

HYGIENE AND SECURITY:

- Non-flammable product. Very low toxicity to mammals, despite their high insecticidal activity.
- Because contain no toxic product, no precautions are necessary in this regard during its application. If applied by spray mask is recommended.
- It should not apply in very cold weather where there are temperatures below or close to 0 ° C. Preserves the paint can of frost.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Comments

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addition proportionally modifies the solid content of the painting and thus the wet film thickness.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.