



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16  
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## FIBRAPRIN - 50 ACRYLIC FIBERS RUBBER

### PRODUCT DESCRIPTION:

- **DEFINITION:** It is an elastic waterproof, acrylic nature and incorporated fiberglass, which give it greater resistance when forming a multidirectional film at the surface.
- **USE:** For all kind of work in waterproofing terraces, roofing, walls, deck, flat roof, roof and jardiniere, which require to prevent moisture and water infiltration and can be applied on any kind of material such as mortar, brick, concrete, asbestos cement, tile, wood, cardboard, etc.
- **PROPERTIES:** Very good adhesion and waterproof provided by the waterproofing acrylic nature. It also presents a high flexibility and elasticity due to the plasticizers that are involved in its manufacture. It is resistant to weather and stable to temperature changes.

### TECHNICAL INFORMATION

Aspect.....	SATIN
Color.....	WHITE, RED and GRAY
Density.....	1,3 – 1,4 Kg/Lt.
Viscosity.....	125 K.U.
Theoretical performance.....	2 M <sup>2</sup> /Kg.
Drying 20 °C/70% RH	
Touch.....	2 HOURS
Overall .....	4 HOURS
Repaint.....	12 HOURS

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush, Roller, Airbrush gun or Air-Less.
- **Dilution**  
If necessary use only water.
- **Cleaning**  
After use, clean all equipment with water, preferably hot.

### SURFACES PREPARATION:

The surface must be clean, dry, without grease and oils and be consistent. If there is parts that shelling, it is necessary to eliminate them. The first-coat of FIBRAPRIN, is diluted in water, up to 15%. After that, one or two coats of FIBRAPRIN slightly diluted or as it are used, until get a thickness of 200 - 400 microns. It is advisable to apply the successive coats in a crossed form for better treatment outcome.

### HYGIENE AND SECURITY:

- Nonflammable product.
- Due to it solvent is water, does not present any toxicity problems.
- Should not be applied in very cold weather, where temperatures are near or below 5° C.
- Preserve paint can from frost.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

### Comments

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addiction proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.