



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



LUCASAC - 525

PRODUCT DESCRIPTION:

- **DEFINITION:** It's a high quality acrylic paint to protect and decorate exterior and interior surfaces.
- **USE:** On masonry surfaces (plaster, cement, tile, concrete...) as well as metal and wood (with previous preparation or priming).
- **PROPERTIES:** Shows high resistance to alkali and weather, with waterproofing qualities of great power. It is characterized by its great performance, whiteness, coverage, and clean ability. Due to a balanced viscosity profile and great power of humidity retention, a perfect application can be obtained, even in absorbent base.

TECHNICAL INFORMATION

Aspect..... MATTE
 Color..... Snow white
 Density..... 1,4 Kg/Lt
 Viscosity..... 95 – 105 K.U. 25°C
 Theoretical performance..... 8 - 10 M²/Kg by coat,
 according to surface.
 Drying 20 °C/70% RH
 Touch..... 1 hour
 Repaint..... 2 -3 hours

APPLICATION INSTRUCTIONS:

- **Brush and roller**
Can be diluted up to 5%
- **Airbrush gun**
Diluted in the range 5-10%
Pressure: 3 – 4 Kg/cm² **Nozzle:** 1,5 - 2 mm.
- **Airless spray**
Diluted in the range 5-10%
Pressure: 170 – 180 Kg/cm² **Nozzle:** 0,35 - 0,45 mm.
- **Cleaning material and dilution**
Clean with water immediately after use.

SURFACES PREPARATION:

Remove imperfections and adhesions, sanding and cleaning to remove salt, grease, old paint, dust...

- **NEW SURFACES:**
 - 1 – **Hard and dry surfaces** indoor and outdoor masonry: Apply TWO COATS (the first diluted to 10% and the second one undiluted or maximum 5%) of LUCASAC – 525.
 - 2 – **Soft or very absorbent surfaces:** Apply one coat of VITREN SEALANT and after that TWO COATS of LUCASAC – 525.
 - 3 – **Wood.** Previously apply ONE COAT of VITREN SEALANT and after ONE or TWO COATS of our LUCASAC - 525.
 - 4 – **Iron.** Previously apply one coat of PRIMER and passed 24 hours TWO COATS of our LUCASAC – 525

Repaints over tempera, old paints, etc.

After removing peeling, tempera, lime,... apply TWO COATS (the first one diluted to 10% and the second one undiluted or maximum 5%) of LUCASAC – 525.

HYGIENE AND SECURITY:

- Nonflammable product.
- For a reason that it is not a toxic product, it's not necessary to take precautions in this aspect.
- In case it will apply by airbrush gun or airless spray, it is recommended use a mask.
- Do not use in cold weather where temperatures use to be near or less than 0°C.
- Keep the paint can far from freeze temperatures.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover. In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product to fall out of our reach and control the conditions and circumstances of the application.