



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



PLASINT - 25

PRODUCT DESCRIPTION:

- **DEFINITION:** Acrylic paint for interior decoration washable and high transpiration.
- **USE:** On masonry surfaces (plaster, plasterboard, cement, brick, concrete...) and wood and metal (with previous preparation and primer required).
- **PROPERTIES:** It has a soft touch matte finish, with good covering and whiteness power. It has a thixotropic type viscosity, which delivers very ease application.

TECHNICAL INFORMATION

Aspect.....MATTE
 Color.....WHITE
 Density.....1,6 Kg/Lt
 Viscosity.....110 – 120 K.U.
 Theoretical performance.....6 - 8 M²/Kg by COAT, ACC SURFACE.
 Drying 20 °C/70% RH
 Touch.....1 HOUR
 Repaint.....4 HOURS

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun or Air-Less.
- **Dilution**
If necessary use only water.
- **Cleaning**
After use, clean all equipment with water
- **Storage**
Original containers tightly closed, four years.
It can be stored in environments with high humidity and temperatures rates.

SURFACES PREPARATION:

Remove imperfections and adhesions, sanding and cleaning to remove nitrate deposits, grease, old paint, dust ...

• NEW SURFACES.

- 1 – HARD, DRY SURFACES and NEW CHARGES of interior masonry. Apply TWO COATS of PLASINT – 25.
- 2 – SOFT SURFACES (plaster wrong setting), or VERY ABSORBENT give a good preparation to plug the pores, as LATEX SEALER ALKYL and then TWO COATS of PLASINT – 25.
- 3 – WOOD. Previously apply one pre-diluted COAT and then TWO COATS of PLASINT - 25.
- 4 – IRON. Beforehand apply one PRIMER COAT and after 24 hours TWO COATS of PLASINT - 25.

• RECOATINGS on TEMPERA, OLD PAINTINGS, ETC.

After removing the peeling, tempera, lime, etc. apply one COAT of VITREN SEALER and then TWO COATS of PLASINT 25.

HYGIENE AND SECURITY:

- Non-flammable product.
- Because contain no toxic product, no precautions are necessary in this regard.
- If applied by spray mask is recommended.
- It should not apply in very cold weather where there are temperatures below or close to 0 ° C.
- Preserves the paint can of frost.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Comments

- When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- The addition of water modifies the solid content of the painting and thus the wet film thickness.
- Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover. In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.