



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



ANTI MOLD EXTERIOR PLASTIC

PRODUCT DESCRIPTION:

- **DEFINITION:** It is a high covering plastic paint, ideal for decoration and protection of exterior and interior surfaces which incorporates a fungicide - anti mold additive universal type.
- **USE:** On all masonry surfaces such as plaster, stucco, brick, concrete, etc., where mildew may occur.
- **PROPERTIES:** Fungicide and anti mold. It is a painting based on a stable dispersion of pigments in an acrylic resin emulsion film. Once dry, it gets an excellent water resistance, opacity, whiteness and adhesion.

TECHNICAL INFORMATION

Aspect..... SATIN
 Color..... WHITE
 Density..... 1,3 Kg/Lt.
 Viscosity..... 120 K.U. 25° C
 Theoretical performance..... 10 M²/Kg.
 Drying 20 °C/70% RH
 Touch..... 1 HOUR
 Overall..... 4 HOURS

APPLICATION INSTRUCTIONS:

- **Brush and roller**
The first coat is diluted to about 20% and the second at 5 or 10%.
- **Airbrush gun**
Diluted to the necessary amount to adjust the viscosity.
Pressure: 3 – 4 Kg/cm² **Nozzle:** 1,5 - 2 mm.
- **Cleaning material and dilution**
Clean with water immediately after use.

SURFACES PREPARATION:

Remove imperfections and adhesions, sanding to remove nitrate deposits, grease, old paint, dust ...

- **NEW SURFACES.**
 - 1 – **HARD and DRY SURFACES** of interior and exterior masonry. Apply **TWO COATS** (the first one diluted to 20% and the second at 5 or 10%).
 - 2 – **SOFT SURFACES** (plaster wrong setting), or **VERY ABSORBENT**.
Give a good preparation to plug the pores, with Sandstone Sealant or Vitren Sealer and then **TWO COATS** of **ANTI MOLD PAINT**.
 - 3 – **WOOD**. Previously apply one **VITREN SEALANT COAT** and then **ONE or TWO COATS** of **ANTI MOLD PAINT**.
 - 4 – **IRON**. Beforehand apply one **PRIMER COAT** and after 24 hours **TWO COATS** of **ANTI MOLD PAINT**.
- **RECOATINGS** on **TEMPERA, OLD PAINTINGS, ETC.**
After removing the peeling, tempera, lime... apply **TWO COATS** of **ANTI MOLD**.

HYGIENE AND SECURITY:

- Non-flammable product.
- Because contain no toxic product, no precautions are necessary in this regard.
If applied by spray, mask is recommended.
- It should not apply in very cold weather where there are temperatures below or close to 0 ° C.
Preserves the paint can of frost.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.