



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



INTERIORS ANTI MOLD

PRODUCT DESCRIPTION:

- **DEFINITION:** High quality acrylic paint for interior where mildew may occur.
- **USE:** On masonry surfaces (plaster, stucco, cement, brick, concrete...) and where mildew may occur.
- **PROPERTIES:** Plastic fungicide and anti mold. It features high resistance to alkali and weather, with waterproof qualities of great power. It is characterized by its high performance, whiteness, covering and washability. Due to a balanced viscosity profile and the great power of moisture retention it can achieve a perfect application even on absorbent base coat.

TECHNICAL INFORMATION

Aspect.....	MATTE
Color.....	SNOW WHITE
Density.....	1,5 Kg/Lt.
Viscosity.....	110 K.U. at 25° C
Theoretical performance.....	10 M ² /Kg by COAT, ACC SURFACE.
Drying 20 °C/70% RH	
Touch.....	1 HOUR
Repaint.....	2 - 3 HOURS

APPLICATION INSTRUCTIONS:

- **Brush and roller**
It can be diluted up to 5 %.
- **Airbrush gun**
It is diluted in the range of 5 to 10 %.
Pressure: 3 – 4 Kg/cm² **Nozzle:** 1,5 - 2 mm.
- **Airless spray**
It is diluted in the range 5-10%
Pressure: 170 – 180 Kg/cm² **Nozzle:** 0,35 - 0,45 mm.
- **Cleaning material and dilution**
Clean with water immediately after use.

SURFACES PREPARATION:

Remove imperfections and adhesions, sanding to remove nitrate deposits, grease, old paint, dust ...

- **NEW SURFACES.**
 - 1 – HARD and DRY SURFACES of interior and exterior masonry. Apply TWO COATS (the first one diluted to 10% and the second undiluted or up to 5 %) of INTERIOR ANTI MOLD.
 - 2 - SOFT SURFACES or VERY ABSORBENT. Apply one coat of VITREN SEALER and then TWO COATS of INTERIOR ANTI MOLD.
- **RECOATINGS on TEMPERA, OLD PAINTINGS, ETC.**
After removing the peeling, tempera, lime... apply TWO COATS (the first one diluted to 10% and the second undiluted or up to 5 %) of INTERIOR ANTI MOLD.

HYGIENE AND SECURITY:

- Non-flammable product.
- Because contain no toxic product, no precautions are necessary in this regard.
- If applied by spray mask is recommended.
- It should not apply in very cold weather where there are temperatures below or close to 0 ° C.
- Preserves the paint can of frost.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.