



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)
TELÉF.S.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS
E-mail: eupines@terra.es



ESINTG - 225

PRODUCT DESCRIPTION:

- **DEFINITION:** It is synthetic enamel formed by a mixture of alkyd resins and pigments of high solidity to light and bad weather.
- **USE:** As a finished layer of industrial painting process and in protection of elements exposure on bad weather in maritime, agricultural and mining type environment.
- **PROPERTIES:** Its high quality provides excellent brightness and coverage, as well as strong resistance in outdoor and indoor environments. It presents a very good equalization, leveling surfaces and application properties.

TECHNICAL INFORMATION

Aspect..... HIGH GLOSS
 Color..... ALL RAL COLOR
 CHART F3
 Density..... 1,05 – 1.15 Kg/Lt.
 Viscosity.....65 – 75 K.U.
 Volume solids..... 45%
 Recommended thickness.....30 micron
 Theoretical performance..... 15 M²/Kg
 Drying 20 °C/70% RH
 Touch..... 1 - 2 hours
 Repaint..... 12 hours

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun, Air-Less
- **Dilution**
If necessary use our Universal Solvent.
- **Cleaning**
After use, clean all equipment with our Solvent S.G.

SURFACES PREPARATION:

The product had to be applied on properly primed surfaces. The priming surface should be clean, dry and free of grease. In slightly rusty surfaces, apply a good layer of our LYMUSE - 125 or H – 200.
 In blasted and cleaned surfaces apply IXIMA – 2/C or H – 400 leaving dry for 24 hours before applying ESINTG – 225.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Comments

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addiction proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.