



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



SILESMALT – 100 OUTDOOR BRIGHT ALUMINUM

PRODUCT DESCRIPTION:

- **DEFINITION:** Enamel formulated based on modified synthetic resins and high quality aluminum pigments.
- **USE:** As a finishing coat on metal surfaces both indoors and outdoors.
- **PROPERTIES:** Excellent decorative effect due to its high degree of light reflection and metallic shine.

TECHNICAL INFORMATION

Aspect.....	BRIGHT
Color.....	ALUMINUM GRAY
Density.....	1 Kg/Lt.
Viscosity.....	70 – 75 K.U.
Volume solids.....	45%
Recommended thickness.....	20 - 25 micron
Theoretical performance.....	18 – 22.5 M ² /Lt.
Drying 20 °C/70% RH	
Touch.....	30 MINUTES
Overall.....	2 HOURS
Repaint.....	12 HOURS
Thermal resistance.....	100° C Continuous

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun, Air-Less
- **Dilution**
If necessary use our D-307 Solvent.
- **Cleaning**
After use, clean all equipment with our Solvent S. G.

SURFACES PREPARATION:

The surface to be treated must be primed with Lymuse-125 or other similar anti-corrosion primer. If is wanted to get a perfect finish, it should be convenient give two coats of Silesmalt – Bright Aluminum of outdoor.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.