



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



TERFON - 150

PRODUCT DESCRIPTION:

- **DEFINITION:** It is a synthetic antioxidant of lead minium based primer, suitable extenders and a good combination of modified resins and oils.
- **USE:** It is used on surfaces of iron, steel and wood in marine and industrial environments.
- **PROPERTIES:** It has a high wetting power which makes it very suitable for the painting of surfaces which preparation is not very careful and for work maintenance on old steel.

TECHNICAL INFORMATION

Aspect.....	MATTE
Color.....	ORANJE
Density.....	2
Viscosity.....	80 – 90 K.U.
Volume solids.....	56%
Recommended thickness.....	40 micron
Theoretical performance.....	14 M ² /Lt.
Drying 20 °C/70% RH	
Touch.....	2 HOURS
Overall.....	8 HOURS
Repaint.....	24 HOURS

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun, Air-Less
- **Dilution**
If necessary use our S.G. Solvent.
- **Cleaning**
After use, clean all equipment with our S. G. Solvent

SURFACES PREPARATION:

- **Iron and steel**
In rural, industrial or indoor environment it is enough a manual or mechanic preparation.
If the surface is highly oxidized, it is recommended a cleaning with sand blasting to grade Sa 2.
- **Non-ferrous metals**
For aluminum, stainless steel, galvanized steel and others non-ferrous metals it is necessary use special treatments.
- **Wood**
In case it is a new wood should be applied a thin diluted coat, to achieve a good penetration.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.
In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.