



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



VARNISH – P – 188 - K SPECIAL FOR STONE AND BRICK

PRODUCT DESCRIPTION:

- **DEFINITION:** Protective stone especially formulated with acrylic resin solvent-borne, for indoor and outdoor.
- **USE:** As waterproofing for waterproof, beautifying and polishing all types of stone surfaces such as brick sandstone, natural stone, concrete, etc.
- **PROPERTIES:** Large capacity impregnation. It prevents the blooms of the soluble salts, reduces the thermal conductivity, thereby creating a better thermal insulation. It reduces the walls tendency to get dirty. Avoid humidity and harden surfaces, etc.

TECHNICAL INFORMATION

Aspect.....	SEMI-BRIGHT
Color.....	COLORLESS
Interval between layers.....	5 hours
Viscosity.....	15" Ford cup N° 4
Volume solids.....	20% ± 2%
Recommended thickness.....	20 - 25micron
Specific weight	0.910 ± 2%
Max. Temperature Resistance.....	70 ° C
Adhesion.....	100%
Toxicity after dry.....	non-toxic
Average performance.....	6 - 7 M ² /Lt.
Adequate solvent.....	D - 307
Drying 20 °C/70% RH	
Touch.....	30 minutes
Overall.....	12 hours

APPLICATION INSTRUCTIONS:

- **Method**
Apply a first hand diluted to 10% and a second coat as it is, without dilution. In all cases must be made with wool roller or brush. In special cases can be applied by immersion and airbrush gun with nozzle 1 to 1.5 mm. and pressure of 3 to 4 atmospheres.
- **Process**
For each case should be asked the treatment to follow. Before each operation, must homogenize the contents of the package, stirring it.
- **Cleaning**
After use, clean all equipment with our D – 307 Solvent.

SURFACES PREPARATION:

All surfaces should be cleaned of dust and dirt, dry and degreased, therefore we recommend using our S.G. sequestrant-Degreaser of Humidity. When used as a finish, should be applied two coats. When used as a sealant, it is sufficient one coat diluted to 10%. In cases where there are old paintings in poor condition, lack of adherence, and so on, proceed to eliminate them before applying varnish-P188-K. If the paintings were old and were in good condition but there are several layers is preferable to remove them before applying varnish-P188K to avoid possible releasing in some layer.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.