





C.I.F. B/33.124.959
POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)
TELÉFS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS
E-mail: eupines@terra.es































# **VARNISH TYPE I - 10**

### PROTECTIVE VARNISH FOR METALS, TOOLS AND MACHINED PARTS

#### PRODUCT DESCRIPTION:

• **DEFINITION**: Protective film especially made to get a great anticorrosive protection.

• USE: As temporary protection for machined parts and tools that had been previously treated.

• PROPERTIES: Product with resistance to endure for a time to the weather and sea transport. It resists to humid and dry

atmospheres.

#### TECHNICAL INFORMATION

Aspect.....SATIN

RED

 $Density.....0,\!805\;Kg/Lt.$ 

Viscosity......15" Ford cup No 4

Volume solids.....

#### APPLICATION INSTRUCTIONS:

#### Method

Paintbrush, Brush, Roller, Airbrush gun and Air-Less.

#### • Dilution

If necessary use our Varnish Solvent I-10. It is not recommended to be diluted with any kind of Solvent, should be applied as it comes.

#### • Cleaning

After use, clean all equipment with our S.G.Solvent in particular gun and nozzles.

## **SURFACES PREPARATION:**

It is necessary to clean the surfaces of all kinds of dust, dirt, grease and humidity, must be completely dry.

If you want to apply two coats to get more protection it can be applied one after the other, or if you prefer in the next day.

#### **HYGIENE AND SECURITY:**

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 562.84.69.

#### **Comments**

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addiction proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.