



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉF.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



B. P. M. H. - 555

PROTECTIVE VARNISH FOR METALS AND TOOLS

PRODUCT DESCRIPTION:

- **DEFINITION:** Protective film especially manufactured to get a great anticorrosive protection.
- **USE:** As temporary protection for machined parts and tools that had been previously treated.
- **PROPERTIES:** Product with resistance to endure for a time to the weather and sea transport.

TECHNICAL INFORMATION

Aspect..... COLORLESS
 Color..... SATIN
 Density..... 0,900 Kg/Lt.
 Viscosity..... 15" Ford cup N° 4
 Volume solids.....
 Recommended thickness..... 5 - 20 micron
 Theoretical performance..... 12 M²/Lt
 Drying 20 °C/70% RH..... 15 minutes

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun and Air-Less.
- **Dilution**
If necessary use our D - 300 Solvent.
- **Cleaning**
After use, clean all equipment with our S.G. Solvent.

SURFACES PREPARATION:

Clean the surfaces of dirt, grease and humidity.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 - 562.84.69.

Comment

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.