



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



FONDIAQUA - 555

AQUEOUS SANDABLE BASE FOR WOOD

PRODUCT DESCRIPTION:

- **DEFINITION:** It is a mono component varnish, based on acrylic copolymer in aqueous dispersion of physical and thermal drying that provides excellent water resistance film and good repaints as well as great sandability.
- **USE:** As base for treatment of wood parquet in Indoor Sports Facilities.
- **PROPERTIES:** Great covering power and the basis for later apply BARNIAQUA-692. Nontoxic. Not flammable. It not gives off odor.

TECHNICAL INFORMATION

Aspect.....	SILK
Color.....	COLORLESS
p.H.....	6,5 ± 0,2
Viscosity.....	23" FORD CUP N° 4 to 20° C
Volume solids.....	38 - 40%
Theoretical performance.....	8 - 10 M ² /Lt.
Drying 20 °C/70% RH	
Overall.....	3 hours
Repaint.....	2 - 3 hours

APPLICATION INSTRUCTIONS:

- **Method**
Brush or Roller.
- **Dilution**
If necessary use WATER.
- **Cleaning**
After use, clean all equipment and tools with cold water.

SURFACES PREPARATION:

- The surface to be varnished should be clean and free of dust. The temperature at the time of applying the varnish should not be less than 13 ° C. The best use for its application will be with roller and in its absence brush.
- As a first layer, apply **FONDIAQUA-555** and passes 4 hours at 20 ° C sand with vibrate machine and 240-280 grain sandpaper. Then apply 2 or 3 coats of **BARNIAQUA-692**, leaving 2 or 3 hours of drying between layer and layer.
- Under conditions of cold and humidity, prolong drying time reasonably up to 7 hours after application, as not doing so, we may encounter problems with crumpled varnish in the second layer due to an insufficient curing of the film.

HYGIENE AND SECURITY:

- Should shake the product before use.
- Product not flammable. No toxic. It not gives off odor.
- Avoid prolonged inhalation of solvent vapors.
- Store in a cool place to avoid both the cold and the excessive heat.
- Avoid contact with skin and eyes, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 - 562.84.69.

Comments

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.