



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16  
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## NITRO LACQUER SEALER

### PRODUCT DESCRIPTION:

- **DEFINITION:** It is sandable nitrocellulose lacquer to apply as a base for wood treatment.
- **USE:** For protection, decoration and beautification of all sorts of indoor wood
- **PROPERTIES:** High power filler, easy manual or machine sanding, fast drying and good penetration into the pores of the wood.

### TECHNICAL INFORMATION

Aspect.....	BRIGHT, SATIN, MATTE
Color.....	COLORLESS
Density.....	0,9 Kg/Lt.
Viscosity.....	80" Ford cup -4 to 20° C
Volume solids.....	26%
Recommended thickness.....	20 micron
Theoretical performance.....	13 M <sup>2</sup> /Lt.
Drying 20 °C/70% RH	
Touch.....	10 minutes
Overall.....	4 hours
Repaint.....	4 hours

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush , Airbrush Guns, Curtain.
- **Dilution**  
For Brush application is recommended to not add the solvent. For gun application add a 3-5% of our Nitro Solvent.
- **Cleaning**  
After use, clean all equipment with our Nitro Solvent.

### SURFACES PREPARATION:

The wood must be clean and dry. It will sand slightly to remove dust, where the woods are two absorbent will be apply two coats of Nitro Lacquer sealer, sanding after each application. Subsequently applied varnish finish.

### HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

### Comment

- \* Do not apply with high relative humidity, low temperatures or wood exposed to cold and wet air flowing.
- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover. In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.