



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## TRAFFIC PAINT

### PRODUCT DESCRIPTION:

- **DEFINITION:** Painting made with various modified resins. It is very adherent and specially indicated for pavement signal.
- **USE:** For their properties, is a product used for all signage types such as urban, industrial, garages, road signs in Public Works, Highways, etc.
- **PROPERTIES:** In all its uses, it achieves excellent resistance to weathering and corrosion, as well as good finish and extraordinary aspect. Adheres on pavements, paved, asphalt and resists abrasion. It supports the steps of constant friction of pallet truck, braking, pneumatic tires, etc. It has good resistance to the outside.

### TECHNICAL INFORMATION

Color.....	WHITE, YELLOW and RED
Aspect.....	MEDIUM GLOSS
Density.....	1,455 Kg/Lt
Volume solids.....	44%
Recommended thickness.....	70 - 80 micron
Theoretical performance.....	6 M <sup>2</sup> /Lt
Lifetime.....	1 Year
Drying 20 °C/70% RH	
Touch.....	5 MINUTES
Overall .....	1 HOUR
Repaint .....	12 HOURS

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush, Roller, Airbrush gun.
- **Dilution**  
If necessary use our X - 843 Traffic Solvent.
- **Cleaning**  
After use, clean all equipment with our S. G. X - 843 Solvent.

### SURFACES PREPARATION:

It should apply in all cases, on clean surfaces, dry and free from grease, dust and humidity. It is convenient mix the product thoroughly before application, stirring five minutes with a clean dry stick.

### HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 - 562.84.69.

### Comment

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.
- \* Being a type-epoxy coating, drying times can vary significantly according to the humidity and temperature at the time of application, and subsequent curing.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.