



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959
POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)
TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS
E-mail: eupines@terra.es



VIAL - 80

PRODUCT DESCRIPTION:

- **DEFINITION:** It is chlorinated rubber paint, very adherent and specially indicated for pavement signal.
- **USE:** For their extraordinary properties, is a product used for all signage types of urban, industrial, garages, road signs in Public Works, Highways, Viaducts, Civil Works in general, zebra steps, curbs, metal signals weakly primed with LYMUUSE, concrete, asbestos cement, Indoor Sports Facilities, etc.
- **PROPERTIES:** In all its uses, it achieves excellent resistance to weathering and corrosion, as well as good finish and extraordinary aspect. Adheres on pavements of cement, paved, asphalt and resists abrasion. It supports the steps of constant friction of pallet truck, braking, pneumatic tires, etc. It has good resistance to the outside. It is equally resistant to diluted acids and alkalis on a regular basis.

TECHNICAL INFORMATION

Color..... WHITE, RED and
YELLOW
Density..... 1.29 Kg/Lt.
Viscosity..... 100 ± 10" FORD CUP 4
Volume solids..... 58%
Recommended thickness..... 50 - 60 micron
Theoretical performance..... 5 M²/Lt.
Drying 20 °C/70% RH
Touch..... 45 MINUTES
Overall 12 HOURS
Repaint 24 HOURS

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun and Air-Less.
- **Dilution**
If necessary use our S.G. Solvent.
- **Cleaning**
After use, clean all equipment with our S.G. Solvent.

SURFACES PREPARATION:

It should apply in all cases, on clean surfaces, dry and free from grease, dust and humidity. It is convenient mix the product thoroughly before application, stirring five minutes with a clean dry stick.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Comment

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover. In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.