



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉF.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## GRAINED PAINTING INTERIOR-EXTERIOR WOOD FINISH

### PRODUCT DESCRIPTION:

- **CHARACTERISTICS:** Satin enamel with polyurethane. Let's get in a single layer the hardwood tone and grained on any smooth, nonporous surface.
- **USE:** Appliances, wainscot, furniture, doors, windows etc. as well as on plastic, Formica and metal.
- **PROPERTIES:** Easy application, quick drying and hardening, provides silky, smooth and hard touch from hardwoods. It is washable, resistant to stains and scratches.

### TECHNICAL INFORMATION

|               |   |
|---------------|---|
| Color.....    | according our catalog                             |
| Drying.....   | from 4 to 6 hours                                 |
| Repaint.....  | 24 hours minimum                                  |
| Solvent.....  | S. G. type  |
| Useful.....   | brush and mottler                                 |
| Cleaning..... | S. G. type  |
| Yield.....    | from 9 to 11 m <sup>2</sup> per liter<br>and coat |

### SURFACES PREPARATION:

On paint in good condition:

1. – Wash and sand the surface
2. – Apply our GRAINED PAINTING

On paint in poor condition:

1. – Remove paint
2. – Putty the defects
3. – Proceed as in new areas

### APPLICATION INSTRUCTIONS:

1. – Surface must be clean and dry
2. – Shake well the container. Do not dilute
3. – Apply with flat and wide brush of 6 or 8 cm (Mottler). With a stiff bristle mottler, uneven and little hair can get the best grain.
4. – Give a generous coating, spread the paint and finally use the brush in the direction of desired graining. Do not paint large areas at once.
5. – To highlight the veins, drain the brush and skim the surface with the tip of the bristles in continuous parallel or wavy lines, but in the same direction. When it begins to dry (approx. 15 minutes) do not attempt corrections, wait for total drying and make a new application. The joints should be achieved in parallel to the grain.

### HYGIENE AND SECURITY:

- No suitable for domestic use.
- Not suitable for use in schools or child.
- Contains aliphatic hydrocarbons, aromatic authorized and Xylene.
- Warning: Toxic by inhalation. Risk of serious damage to health by prolonged exposure. Keep out of reach of children. If the product splash eyes, rinse with water several times and consult the doctor or the National Toxicology Institute: 915628469.
- Flammable. Keep this container away from fire. Cover after its use.

Our Technical Support is always available to expand the information in this brochure as well as to advise on special treatments, systems, processes and products best suited according to the surface, environments and needs.

With this data sheet, based on experience and research, we just try to inform and advise as our knowledge and belief. We can not take responsibility for the consequences of using this product to fall outside of our control.