



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959  
POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)  
TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16  
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS  
E-mail: eupines@terra.es



## TEAK OIL – 542 - T

### PRODUCT DESCRIPTION:

- **DEFINITION:** The teak oil is a mixture of natural resins, refined oils and specially selected additives.
- **USE:** To cleanse, nourish and enrich all types of wood and especially teak or iroko, and also other exotic tropical wood.
- **PROPERTIES:** Prevents drying and cracking caused by the sun. Also protects against dust, dirt, stains, etc., recovering their natural state and original qualities of texture, color, brightness, etc.

### TECHNICAL INFORMATION

Texture.....	SILKY
Tonality.....	SOFT NATURAL
Color.....	TEAK – CAMELIZED HONEY
Density at 20° C.....	0,87 ± 0,05
Acidity as oleic acid.....	0,5 % MAX.
Gardner Color.....	4 MAX.
mIU.....	0,2 % MAX.
Saponification index.....	189/195
Iodine index.....	180/195
Refraction index at 20° C.....	1.4795/1.4851
Touch Dry.....	6 HOURS
Overall Dry .....	24 HOURS
Repaint Dry .....	12 HOURS
<b>FATTY ACID COMPOSITION (%)</b>	
Palmitic.....	5/9
Stearic.....	2/8
Oleic.....	17/25
Linoleic.....	13/22
Linolenic.....	48/60

### APPLICATION INSTRUCTIONS:

- **Applications fields**  
For maintenance of all types of wood and furniture, both indoor and outdoor, gardens, sports equipment, wood high mountains, etc.
- **Method**  
Brush, Roller, pistol and immersion (check for this last one).
- **Type of packaging**  
1-5-25-50-200 and 1.000 Lt.
- **Cleaning**  
After use, clean all equipment with our S.G. Solvent.
- **Maintenance on our Oil 542 - T**  
No stripping or sanding is necessary, it is sufficient to clean the wood from dust, grease, dirt, etc., and once dry, apply directly a good layer of TEAK OIL -542-T.

### SURFACES PREPARATION AND RECOMMENDATIONS:

To get a good finish is necessary to keep the environment free of dust during application and drying. Previously remove any dust, stains, aged varnishes and paints. Before using the TEAK OIL -542-T is necessary to shake well the bottle.

### HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

### Comments

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.