



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



ACLIN 2. 150 - P

LINSEED OIL 2 – 150 POISE, FLAX SEED OIL

PRODUCT DESCRIPTION:

- **DEFINITION:** It is a Triester of fatty acid and of Thermally Polymerized glycerin.
- **USE:** In all types of chemical and industrial processes, in all kinds of hydraulic pumps, for paints and varnishes formulation, etc.
- **PROPERTIES:** It has great air dry ability and a decrease in yellowing by light and stove drying exposure. The resulting films are very flexible.

TECHNICAL INFORMATION

Type.....	150 POISE ESTANDOI
Acidity index.....	7 -11
Viscosity at 25° C.....	150 ± 10
Gardner Color.....	4 (CAMEL)
Flash point ° C.....	315
Saponification index.....	185 – 195 mg. KOH/g.
Iodine index.....	MIN – 120 g12/100gr.
Refraction index.....	1.483 - 1.488 at 20° C
Presentation.....	OILY PRODUCT
Corrosive.....	NO
Volatile.....	NO

APPLICATION INSTRUCTIONS:

- **Method**
It serves pure and can be used as it is or applying by compressed air gun, brush, etc.
- **Handling and Storage:**
Medium viscosity product; does not require any special handling or storage. Indefinitely stable in full and tightly closed drum.

HYGIENE AND SECURITY:

- In case of fire do not use water jet. Use water spray, dry powder extinguishers, CO₂, foam.
- In case of accidental spillage and for being a greasy product, absorb with sawdust or absorbent soil. Dragging with water and wash with detergent.
- It does not produce fumes, without contraindications to skin contact. Goggles are recommended.
- If swallowed, is not toxic but difficult to digest, manage vomiting or gastric lavage.
- If eye splash occurs wash with plenty of water.
- In case of contact with skin, wash with soap and water.
- Given the slightest doubt, always consult a doctor or the National Toxicology Institute 91-5628469.
- Avoid watercourses contamination and leakage in permeable soils. Do not discharge into sewer.

Comments

- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.