



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉF.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



ANTISILICONE – 459 - SW

PRODUCT DESCRIPTION:

- **DEFINITION:** Liquid product of surfactant character made from silicone with modified Polymers.
- **USE:** In all kinds of paintings that at the time of its application form craters, eyes, etc.
- **PROPERTIES:** Prevents the craters formation, pores and fish eyes. Improve substrate wetting, the leveling of the paint and sometimes acts as a defoamer.

TECHNICAL INFORMATION

Aspect.....	YELLOW CLEAR LIQUID
Color (Gardner 1953).....	5 + MAX.
Denso, 25° C, Kg/m ³	885 – 905
Viscosity, 25° C	
Gardner-Holdt.....	E max.
3mm ISO-cup (40° C).....	> 30 sec.
Volume solids.....	20 %
Solubility.....	Soluble in aliphatic hydrocarbons, aromatic hydrocarbons, ketones, esters and ethers.
Flash point.....	43
(ASTM D3278-98) ° C	

Properties of use

It is used for finishes application on substrates presenting a contamination by oil, grease or silicone. It is advisable for coating systems based on alkyd paints, chlorinated rubber, polyurethane, acrylics, epoxies, etc.

Proportion of use

It is recommended a dose of 0.5 to 1.5% for most applications. In some cases it may be higher. It must be added to the paint and stir thoroughly until complete homogenization.

Handling and storage

It should be kept away from heat and flame. It had to be stored at temperatures below 35 ° C.

Packaging

It's packaged in cans of 1 liter, 5 liters and 25 liters.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Labeling and classification

- * According to EC guidelines:
- * Risk term: R10
- * Security term: S15, S24/25
- * Hazard warning symbol
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.