



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16  
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## AUTOBAJ - THIN LAYER

### PRODUCT DESCRIPTION:

- **DEFINITION:** It is a bituminous painting of industrial type.
- **USE:** It is used for painting metal surfaces that are often located in high humidity environments as outdoor of pipes, bridges and automotive bottom, interior floating docks and hold.
- **PROPERTIES:** As it contains a selection of special asphalts with very good penetration index, perfect finish is achieved with good hardness and adhesion. It has very good resistance to water.

### TECHNICAL INFORMATION

Aspect..... SEMIGLOSS  
 Color.....BLACK  
 Density..... 0.9 – 1 Kg/Lt  
 Viscosity.....75 – 85 K.U.  
 Recommended thickness..... 30 – 40 MICRONS  
 Theoretical performance..... 8 - 10 M<sup>2</sup>/Lt  
 Drying 20 °C/70% RH  
 Touch..... 15 - 30 MINUTES  
 Continuous maximum temperature . 60° C

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush, Roller, Airbrush gun, Air-Less.
- **Dilution**  
If necessary use our D - 302 Solvent.
- **Cleaning**  
After use, clean all equipment with our S.G. Solvent.

### SURFACES PREPARATION:

Perform a manual clean, up to the level St 2.

### HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

### Comments

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.  
 In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.