



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## E. T. P. - 43 GENERAL PAINT STRIPPER

### PRODUCT DESCRIPTION:

- **DEFINITION:** It is a product specifically formulated to eliminate any kind of paint in all kinds of surfaces.
- **USE:** It is used to strip primers, enamels and varnishes on wood and metal surfaces avoiding sanding or manual cleaning.
- **PROPERTIES:** It has a gelatinous appearance. This allows its application throughout the top of surfaces, both horizontally as vertically.

### TECHNICAL INFORMATION

Aspect.....	THIXOTROPIC
Color.....	WHITISH
Minimum time reaction.....	20 - 25 SECONDS
Performance.....	2 M <sup>2</sup> /Kg
Reaction time and removal.....	3 MINUTES
Recommended layer.....	100 MICRONS
Package type.....	1,5 and 20 Kg.
Storage.....	1 YEAR
Effectiveness.....	INDEFINITE

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush, Roller, Airbrush gun, Air-Less.
- **Dilution**  
Spread a good layer on the surface to remove the paint. Wait about three minutes and when it starts to lift, insert a spatula and go removing the stripping film. Repeat the operation as often as necessary until reach the material to be treated. Once all the paint has eliminated, do a good surface wash with our S.G. solvent to remove the resulting waste.
- **Cleaning**  
After use, clean all equipment with our Nitro Solvent ETP-43.

### HYGIENE AND SECURITY:

- During its application, care must be taken, as it has strong solvent, avoiding skin contact. It should be applied with rubber gloves, mask, and good ventilation.
- When you open the packaging, care must be taken, since it is possible the formation of gas inside, which could result in violent dismissal from the lid, with the subsequent detonation.
- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 - 562.84.69.

### Comments

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addiction proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.