



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



DESENCOFRINT - 888

RELEASE AGENT FOR CONCRETE FORMWORK OVER IRON AND WOOD

PRODUCT DESCRIPTION:

- **DEFINITION:** It is oil emulsified in water, for demolding of wood formworks, and metal boards, for concrete.
- **USE:** Releasing of concrete pieces on site, with wood and metal formwork.
- **PROPERTIES:** Easy element release, non-stick high-capacity and good penetration into wood and excellent coverage on metals.

TECHNICAL INFORMATION

Density.....0,97 ± 0.01 Kg./dm³
 Color - appearance.....MILKY
 Presentation.....BOTTLES 25 and 200 Lt.
 Preparation.....READY FOR USE
 Toxicity.....NONTOXIC
 Storage.....12 months in tightly closed original container in a cool dry place, covered and protected from frost.
 Performance.....WOOD: 12 m² Lt.
 IRON: 15 m² Lt.

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun, Air-Less, until wet out the surfaces.
- **Dilution**
If necessary use water.
- **Cleaning**
After use, clean all equipment with plenty water, if is possible with pressured water.

SURFACES PREPARATION:

Wood and metal must be dry, clean of cement dust, removing remnants of previous released, grease, dirt, strange objects, etc. The product should be applied in one or two layers according to wood adsorption or the desired thickness to be applied to the metal. Wait 30 minutes before place the concrete.

Precautions

- Should not apply excessive amounts because they can produce spots in the concrete.
- Ensure that the application is homogeneous across the surface of the casing, extending crosswise.
- The manipulation must be done with rubber gloves and safety glasses.

HYGIENE AND SECURITY:

- Non-flammable product.
- If applied by spray mask is recommended.
- It should not apply in very cold weather where there are temperatures below or close to -2 ° C.
- Preserves the paint can from frost.
- If the product splashes eyes, rinse with clean water several times without scrubbing; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Comments

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.