



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA

PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉF.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



NITRO SOLVENT

PRODUCT DESCRIPTION:

- **DEFINITION:** It is a special solvent compatible with nitro paints, vinyl paints, nitro lacquers, epoxy paints and chromophosphating primers of one component.
- **USE:** It is formulated with a blend of aromatic hydrocarbons, acetates and alcohols.
- **PROPERTIES:** Used for mixing and dilution of nitro paints, epoxy and vinyl and chromophosphating primers of one component. It is also used for cleaning all types of tool used in the application.

TECHNICAL SPECIFICATIONS

Aromatic content.....35 % \pm 2 %
 Color.....COLORLESS
 Density..... 0,85 \pm 0.01 % Kg/Lt.
 Flash point.....5° C \pm 1 %
 Boiling point..... 92° C \pm 1 %
 Ignition temperature.....510° C \pm 1 %
 Melting point..... -96° C \pm 1 %
 CLEAR LIQUID AND VOLATILE AND PLEASANT ODOR
 NOT MISCIBLE WITH WATER AND MORE MILD THAN THIS

Hygiene and security

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.
- Explosive container when heated.
- In case of spillage, prevent sparks or flames, seeking to cut the fire with sand.
- In case of fire, extinguish with foam or chemical powder, but never with water.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.