



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16  
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## EUROCOLA - 1699

### PRODUCT DESCRIPTION:

- **DEFINITION:** It is a modified acrylic dispersion with synthetic resins and special additives.
- **USE:** It's a contact adhesive for glued of PVC tiles, latex, rubber, carpets, vinyl-asbestos, on mosaic, concrete floors, etc.
- **PROPERTIES:** It is a glue of easy application, adequate extensibility, and excellent wet grip, good final glued and excellent performance.

### TECHNICAL INFORMATION

Aspect.....SATIN  
 Color.....GRAY - IVORY  
 Density..... 1,11 Kg/Lt.  
 Viscosity.....260 – 280 POISE  
 Volume solid..... 70 %  
 Recommended thickness..... 60 – 70 MICRON  
 Theoretical performance..... 290 – 330 Gr/m<sup>2</sup>  
 Use..... ONE SINGLE – SIDED  
 Flammability..... NONFLAMMABLE  
 pH.....7 – 7,5  
 Resistance to heat, oils and  
 Plasticizers..... GOOD

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush, Roller, serrated blade of 1 mm.
- **Cleaning**  
After use, clean all equipment with our Eurocola - 1699 Solvent.
- **Type of packaging:** 5,22 and 200 Kg.

### SURFACES PREPARATION:

When applied over concrete / cement the floor must be well leveled and the humidity of this should not exceed 3% and the ambient temperature shall not exceed 8° C. Apply the glue on the floor with a serrated blade 1mm. depth with continuous tooth of 1mm wide, the blade can also be used to apply glue to paste cork tiles in the wall; for carpet will be used a toothed blade with 2 mm in depth and width. The floor shall be free of dust, grease, oils and detergents. Once applied the adhesive and last 30-35 minutes at 20° C, the substrate can be positioned to glue. After placed the coating, give a uniform pressure to achieve full contact. The bonding time depends on temperature and ambient humidity. This glue has hardened and fully vitrified after 24 hours; in the case of PVC tiles, it can be welded past 35 hours of placing the pavement.

### HYGIENE AND SECURITY:

- Non-flammable product.
- Because contain no toxic product, no precautions are necessary in this regard.
- Keep the glue in ambient not below 12° C.
- The glue life is 10-12 months if not suffer frost.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

### Comments

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addition proportionally modifies the solid content in of the glue.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.

In order to improve the E. P. E. product at any time and without prior notice may change the formulation of the same, therefore modifying the TECHNICAL FEATURES of this Sheet.