



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16  
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## H – 200 TYPE: P. O. – 2.000 OXIDE STABILIZER CONVERTER

**STABILIZER CONVERTER** for oxidized metal surfaces which are to be painted. It has the great advantage of NEUTRALIZE the OXIDE of oxidized structures which saves labor and fluids to remove the rust. It stabilizes oxidation transforming the Ferrous Oxide in Ferric Ferrous, i.e. in Magnetite.

### Advantages

1. - Waterproof any metal surfaces.
2. - It neutralizes the rust, being able to paint over.
3. - Mixed with paint, transmits its antioxidant properties to it.
4. - Transform an ordinary painting in anti-corrosive.
5. - Increases paint covering power by 35%.
6. - Great performance, from 6 to 8 m<sup>2</sup> per Kg.
7. - Resist temperatures over 220° C.
8. - Great duration: from 4 to 6 years in adverse conditions.
9. - Communicate more elasticity and penetration to the paint.

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush, Roller, Airbrush gun, Air-Less.
- **Dilution**  
If necessary use our S.G. Solvent.
- **Cleaning**  
After use, clean all equipment with our S.G. Solvent.

Over a new or oxidized structure it forms a hard and flexible film. It penetrates the metal's toughest cavities, extracting the air and moisture, and occupying this place. At the same time, with the rustiness as a pigment.

### Use:

It can be use as a primer coat for a structure to paint in the Merchant Marine, Chemical Industry, etc.

As an additive for all kinds of paints, except for epoxies and chlorinated rubber. Apply the first coat with H - 200 PO-2000 in a pure state, as it is supplied, in all forms of treatment where it appears rusty metal structure, Industrial Machinery, Boiler-making Equipment, Thermal Centrals, etc.

### HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

### Comments

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.