



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959
POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)
TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS
E-mail: eupines@terra.es



J. K. - 25 CLEANER FOR STONE

PRODUCT DESCRIPTION:

- **DEFINITION:** It is a mixture of acid nature components with corresponding inhibitors in order to get a product very suitable for surface cleaning of all types of stone walls.
- **USE:** For general cleaning of all type of stones or any stone material support.
- **PROPERTIES:** Prevents efflorescence of soluble salts, revives the natural color of the stone. It prepares the stone for its further treatment.

TECHNICAL INFORMATION

Aspect..... TRANSPARENT
 Color.....COLORLESS
 Density..... 1,1 Kg/Lt.
 Viscosity.....25" FORD CUP N° 4
 Diluents..... WATER
 Theoretical performance..... 10 M²/Lt.
 Drying time..... 24 HOURS
 Storage..... 1 YEAR

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun, Air-Less.
- **Dilution**
If necessary use water.
- **Cleaning**
After use, clean all equipment with water preferably hot.

SURFACES PREPARATION:

If dirt is too embedded in the rock, it is recommend soak it and then scrubbing with bristle brush or steel wool till get removed the dirt. Then repeat the operation to remove all the dirt in the pores, joints, etc. of the surface.
 Once cleaned, must be made washing with pressurized water and allow drying for 24 hours.
 In order to avoid grasp the dirt, dust, grease, and etc., we recommend apply two coats of our J-13 INVISIBLE WATER - REPELLENT.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 - 562.84.69.

Comments

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addiction proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.