



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA

PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## P. P. P. P. – 850 TIX

### PEELABLE PROTECTIVE PLASTIC FILM FOR FLOORS

#### PRODUCT DESCRIPTION:

- **DEFINITION:** It is a plastic film, protective, peelable with good protection for floors that have to be removed time to time.
- **USE:** As a temporary protector for floors, aluminum foil, etc. It can be removed easily once it has accomplished its mission. Widely used in all kinds of workshops where continually fall resins, powders, grease, etc. to the floor.

#### TECHNICAL SPECIFICATIONS

Aspect.....HALF BRIGHTNESS  
 Color.....ACC/CHART and  
 COLORLESS  
 Density.....1,02 Kg/Lt.  
 Viscosity.....22" FORD CUP N° 4  
 Recommended thickness.....40 MICRAS  
 Theoretical performance.....7 M<sup>2</sup>/Lt.  
 Drying 20 °C/70% RH.....10 MINUTES

#### DRY FILM CHARACTERISTICS:

After 10 minutes of application, dries completely, being able to peel by pulling one end, moving as a continuous film. Do not attack galvanized sheet, stainless steel, anodized aluminum, etc.

#### APPLICATION INSTRUCTIONS:

- **Method**  
Wide brush and Roller.
- **Dilution**  
IS PROVIDED READY FOR USE.
- **Effectiveness**  
Floor protection with periodic disposal.
- **Cleaning**  
After use, clean all equipment with our S.G. Solvent.

#### SURFACES PREPARATION:

Clean surfaces of dirt, dust, grease and moisture.

#### Precautions

In the presence of P.P.P. – 850 TIX vapors it will take the normal precautions against fire.  
 It should retain cans tightly covered, since it is a product whose solvents have a high evaporation rate.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.