



# EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA  
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



## SANIGAL K - 725

### PRODUCT DESCRIPTION:

- **DEFINITION:** Concentrate disinfectant for elimination of fungi, algae and similar on walls and concrete walls, stone, corrugated iron, plaster, cement, asbestos cement, and in general any type of porous material used in construction.
- **USE:** As disinfectant on contaminated walls to remove roots, spores and any remaining pollutants.
- **PROPERTIES:** Because of its high concentration and effectiveness, allows to be used in proportions of 1 to 10 diluted in water. It can be used in most adverse environments both indoors and outdoors.

### TECHNICAL INFORMATION

Aspect.....LIQUID  
 Color.....TRANSPARENT  
 Density..... 1Kg/Lt.  
 Theoretical performance..... 5 - 10 M<sup>2</sup>/Lt.  
 Drying 20 °C/70% RH  
 Touch..... 1 HOUR  
 Overall.....6 HOURS  
 Repaint..... 12 HOURS

### APPLICATION INSTRUCTIONS:

- **Method**  
Brush, Roller.
- **Dilution**  
Dilute from 1 to 10 in water as appropriate to the type of concentration.
- **Cleaning**  
After use, clean all equipment with water.
- **Storage**  
Under cover for 1 year at room temperature and without freezing.
- **Packaging type**  
1 - 5 - 25 - 200 Liters.

### SURFACES PREPARATION:

- Wash with plenty water and let to dry 24 hours before applying the product.

### HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times.
- In case of accidental ingestion consult your doctor or the National Institute of Toxicology, Phone Number 91 - 562.84.69.

### Comments

- \* When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- \* The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- \* Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.